

## **KAWASAKI NINJA 300 TECHNICAL SPECIFICATIONS**

### **ENGINE**

Type: Liquid-cooled, 4-stroke Parallel Twin

Displacement: 296 cm<sup>3</sup>

Bore and Stroke: 62.0 x 49.0 mm

Compression ratio: 10.6:1

Valve system: DOHC, 8 valves

Fuel system: Fuel injection:  $\varnothing$ 32 mm x 2 (Keihin), with dual throttle valves

Ignition: Digital

Starting: Electric

Lubrication: Forced lubrication, wet sump

Transmission: 6 speed, return

Maximum power: 29.0 kW {39 PS} / 11,000 rpm

Maximum torque: 27.0 N.m {2.8 kgf.m} / 10,000 rpm

### **FRAME, TYRES, BRAKES**

Type: Tube diamond, steel

Wheel travel: Front: 120 mm

Rear: 132 mm

Tyre: Front: 110/70-17 M/C 54S

Rear: 140/70-17 M/C 66S

Brake Front: Type: Single 290 mm petal disc

Caliper: Single balanced actuation dual-piston

Brake Rear: Type: Single 220 mm petal disc

Caliper: Dual-piston

### **DIMENSIONS**

Overall length: 2,015 mm

Overall width: 715 mm

Overall height: 1,110 mm

Wheelbase: 1,405 mm

Ground clearance: 140 mm

Seat height: 785 mm

Curb mass: 172 kg

Fuel capacity: 17 Litres